

Gun Powder Missile

Auto Klene Solutions

Chemwatch: 5170-85
Version No: 8.1.1.1
Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 26/09/2024
Print Date: 01/10/2024
S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Gun Powder Missile
Synonyms	Not Available
Proper shipping name	CORROSIVE LIQUID, N.O.S. (contains (C10-16)alkylbenzenesulfonic acid, phosphoric acid, sulfuric acid and acetic acid glacial)
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Car wash presoak. Use according to manufacturer's directions.
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	Auto Klene Solutions
Address	51/885 Mountain Hwy Bayswater VIC 3153
Telephone	+61 3 8761 1900
Fax	+61 3 8761 1955
Website	http://www.autoklene.com
Email	info@autoklene.com

Emergency telephone number

Association / Organisation	Auto Klene Solutions
Emergency telephone numbers	131 126 (Poisons Information Centre)
Other emergency telephone numbers	0800 764 766 (New Zealand Poisons Information Centre)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture



HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	4		0 = Minimum
Body Contact	3		1 = Low
Reactivity	1		2 = Moderate
Chronic	0		3 = High
			4 = Extreme

Poisons Schedule	S6
Classification [1]	Metal Corrosion Category 1, Acute Toxicity (Inhalation) Category 1, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Acute Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	 
---------------------	---

SIGNAL WORD	DANGER
-------------	--------

Hazard statement(s)

H290	May be corrosive to metals.
H330	Fatal if inhaled.
H314	Causes severe skin burns and eye damage.

Continued...

H402	Harmful to aquatic life.
------	--------------------------

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P234	Keep only in original container.
P273	Avoid release to the environment.
P284	Wear respiratory protection.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P320	Specific treatment is urgent (see advice on this label).
P363	Wash contaminated clothing before reuse.

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7664-38-2	10-30	phosphoric acid
64-19-7	1-10	acetic acid glacial
68584-22-5	1-10	(C10-16)alkylbenzenesulfonic acid
7664-93-9	1-10	sulfuric acid
34590-94-8	1-10	dipropylene glycol monomethyl ether
Not Available	balance	Ingredients determined not to be hazardous

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none">▶ Immediately hold eyelids apart and flush the eye continuously with running water.▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.▶ Transport to hospital or doctor without delay.▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none">▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.▶ Quickly remove all contaminated clothing, including footwear.▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.▶ Transport to hospital, or doctor.
Inhalation	<ul style="list-style-type: none">▶ If fumes or combustion products are inhaled remove from contaminated area.▶ Lay patient down. Keep warm and rested.▶ Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.▶ Transport to hospital, or doctor.▶ Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.▶ Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).▶ As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. <p>This must definitely be left to a doctor or person authorised by him/her.</p>

Gun Powder Missile

	(ICSC13719)
Ingestion	<ul style="list-style-type: none"> For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

for phosphate salts intoxication:

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.
- Ingestion of large quantities of phosphate salts (over 1.0 grams for an adult) may cause an osmotic catharsis resulting in diarrhoea and probable abdominal cramps. Larger doses such as 4-8 grams will almost certainly cause these effects in everyone. In healthy individuals most of the ingested salt will be excreted in the faeces with the diarrhoea and, thus, not cause any systemic toxicity. Doses greater than 10 grams hypothetically may cause systemic toxicity.
- Treatment should take into consideration both anionic and cation portion of the molecule.
- All phosphate salts, except calcium salts, have a hypothetical risk of hypocalcaemia, so calcium levels should be monitored.

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling.
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the desiccating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.**
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. **DO NOT use neutralising agents or any other additives.** Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	<ul style="list-style-type: none"> Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acid smoke. <p>Decomposition may produce toxic fumes of:</p> <p>carbon dioxide (CO₂)</p> <p>phosphorus oxides (PO_x)</p> <p>sulfur oxides (SO_x)</p> <p>other pyrolysis products typical of burning organic material.</p>
HAZCHEM	2X

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

Continued...

See section 12

Methods and material for containment and cleaning up

Minor Spills	<div>Environmental hazard - contain spillage.</div> <div><div>▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</div><div>▶ Check regularly for spills and leaks.</div><div>▶ Clean up all spills immediately.</div><div>▶ Avoid breathing vapours and contact with skin and eyes.</div><div>▶ Control personal contact with the substance, by using protective equipment.</div><div>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</div><div>▶ Wipe up.</div><div>▶ Place in a suitable, labelled container for waste disposal.</div></div>
Major Spills	<div>Environmental hazard - contain spillage.</div> <div><div>▶ Clear area of personnel and move upwind.</div><div>▶ Alert Fire Brigade and tell them location and nature of hazard.</div><div>▶ Wear full body protective clothing with breathing apparatus.</div><div>▶ Prevent, by any means available, spillage from entering drains or water course.</div><div>▶ Consider evacuation (or protect in place).</div><div>▶ Stop leak if safe to do so.</div><div>▶ Contain spill with sand, earth or vermiculite.</div></div>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<div><div>▶ DO NOT allow clothing wet with material to stay in contact with skin</div><div>▶ Avoid all personal contact, including inhalation.</div><div>▶ Wear protective clothing when risk of exposure occurs.</div><div>▶ Use in a well-ventilated area.</div><div>▶ Avoid contact with moisture.</div><div>▶ Avoid contact with incompatible materials.</div><div>▶ When handling, DO NOT eat, drink or smoke.</div><div>▶ Keep containers securely sealed when not in use.</div></div>
Other information	<div><div>▶ Store in original containers.</div><div>▶ Keep containers securely sealed.</div><div>▶ Store in a cool, dry, well-ventilated area.</div><div>▶ Store away from incompatible materials and foodstuff containers.</div><div>▶ Protect containers against physical damage and check regularly for leaks.</div><div>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</div></div>

Conditions for safe storage, including any incompatibilities

Suitable container	<div><div>▶ DO NOT use aluminium or galvanised containers</div><div>▶ Check regularly for spills and leaks</div><div>▶ Lined metal can, lined metal pail/ can.</div><div>▶ Plastic pail.</div><div>▶ Polyliner drum.</div><div>▶ Packing as recommended by manufacturer.</div><div>▶ Check all containers are clearly labelled and free from leaks.</div></div> <div>For low viscosity materials</div> <div><div>▶ Drums and jerricans must be of the non-removable head type.</div><div>▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.</div></div> <div>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):</div> <div><div>▶ Removable head packaging;</div><div>▶ Cans with friction closures and</div><div>▶ low pressure tubes and cartridges</div></div> <div>may be used.</div> <div>-</div> <div>Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</div>
Storage incompatibility	<div><div>▶ Reacts vigorously with alkalis</div><div>▶ Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.</div><div>▶ Segregate from alkalies, oxidising agents and chemicals readily decomposed by acids, i.e. cyanides, sulfides, carbonates.</div><div>▶ Avoid strong bases.</div></div>

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	phosphoric acid	Phosphoric acid	1 mg/m3	3 mg/m3	Not Available	Not Available
Australia Exposure Standards	acetic acid glacial	Acetic acid	10 ppm / 25 mg/m3	37 mg/m3 / 15 ppm	Not Available	Not Available


Australia Exposure Standards	sulfuric acid	Sulphuric acid	1 mg/m3	3 mg/m3	Not Available	Not Available
Australia Exposure Standards	dipropylene glycol monomethyl ether	(2-Methoxymethylethoxy) propanol	50 ppm / 308 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
phosphoric acid	Phosphoric acid	Not Available	Not Available	Not Available
acetic acid glacial	Acetic acid	Not Available	Not Available	Not Available
sulfuric acid	Sulfuric acid	Not Available	Not Available	Not Available
dipropylene glycol monomethyl ether	Dipropylene glycol methyl ether	150 ppm	1700 ppm	9900 ppm

Ingredient	Original IDLH	Revised IDLH
phosphoric acid	1,000 mg/m3	Not Available
acetic acid glacial	50 ppm	Not Available
(C10-16)alkylbenzenesulfonic acid	Not Available	Not Available
sulfuric acid	15 mg/m3	Not Available
dipropylene glycol monomethyl ether	600 ppm	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none">▶ Chemical goggles.▶ Full face shield may be required for supplementary but never for primary protection of eyes.▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none">▶ Wear chemical protective gloves, e.g. PVC.▶ Wear safety footwear or safety gumboots, e.g. Rubber▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none">▶ Overalls.▶ PVC Apron.▶ PVC protective suit may be required if exposure severe.▶ Eyewash unit.▶ Ensure there is ready access to a safety shower.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: **"Forsberg Clothing Performance Index"**.
The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:
Gun Powder Missile

Material	CPI
NEOPRENE	A
NITRILE+PVC	A
PE	A
PVC	A

Respiratory protection

Type ABE-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	ABE-AUS P2	-	ABE-PAPR-AUS / Class 1 P2
up to 50 x ES	-	ABE-AUS / Class 1 P2	-

Gun Powder Missile

SARANEX-23	A
NATURAL RUBBER	B
NATURAL+NEOPRENE	B
NITRILE	B
BUTYL	C
BUTYL/NEOPRENE	C
NAT+NEOPR+NITRILE	C
NEOPRENE/NATURAL	C
PE/EVAL/PE	C
TEFLON	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

up to 100 x ES	-	ABE-2 P2	ABE-PAPR-2 P2 ^
----------------	---	----------	-----------------

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear to tan coloured liquid; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	1	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	▶ Contact with alkaline material liberates heat
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Although it has not been demonstrated that the material produces harm following inhalation, unusual routes of exposure have produced damage to the health of at least one animal species. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Minor acetic acid exposure may cause temporary loss of voice while severe acute vapour exposure may cause fluid accumulation in the lungs. Exposure at 800-1200 ppm cannot be tolerated longer than 3 minutes. Inhalation of the vapour may cause choking, coughing, headache, weakness and dizziness, and with long term exposure, fluid accumulation in the lungs and blueness, initially in the fingertips.
----------------	--

Ingestion	The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Ingestion of acetic acid may cause delayed stomach, intestinal and oesophageal perforation, and death in severe cases.
Skin Contact	The material can produce chemical burns following direct contact with the skin. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Action of acetic acid on the skin may be delayed and insidious.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely. Acetic acid produces eye irritation at concentrations below 10 ppm.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Prolonged or repeated skin contact may cause degreasing, followed by drying, cracking and skin inflammation. Repeated minor exposure to acetic acid by mouth can cause blackening of the skin and teeth, erosion of the teeth, vomiting, diarrhea and nausea. Repeated minor vapour exposure may cause chronic inflammation of the airways and bronchitis. Results from testing are mixed, with one report indicating only slight irritation to the airways, stomach and skin, while another reported inflammation of the conjunctiva, bronchi, pharynx and erosion of teeth. Exposure to higher levels caused blackening and hyperkeratosis of the skin and hands. Heartburn and constipation have also been reported with prolonged exposures. Strong inorganic acid mists containing sulfuric acid can cause cancer.

Gun Powder Missile	TOXICITY	IRRITATION
	Not Available	Not Available
phosphoric acid	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >1260 mg/kg ^[2]	Eye (rabbit): 119 mg - SEVERE
	Inhalation (rat) LC50: 0.0255 mg/l/4h ^[2]	Eye: adverse effect observed (irritating) ^[1]
	Oral (rat) LD50: 1250 mg/kg ^[2]	Skin (rabbit):595 mg/24h - SEVERE
acetic acid glacial	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 1060 mg/kg ^[2]	Eye (rabbit): 0.05mg (open)-SEVERE
	Inhalation (rat) LC50: 11 mg/l/4h ^[2]	Skin (human):50mg/24hr - mild
	Oral (rat) LD50: 3310 mg/kg ^[2]	Skin (rabbit):525mg (open)-SEVERE
(C10-16)alkylbenzenesulfonic acid	TOXICITY	IRRITATION
	dermal (rat) LD50: 530-1060 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]
	Oral (rat) LD50: 530-1060 mg/kg ^[2]	Skin: adverse effect observed (corrosive) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
sulfuric acid	TOXICITY	IRRITATION
	Inhalation (guinea pig) LC50: 0.036 mg/l/8h ^[2]	Eye (rabbit): 1.38 mg SEVERE
	Oral (rat) LD50: 2140 mg/kg ^[2]	Eye (rabbit): 5 mg/30sec SEVERE
dipropylene glycol monomethyl ether	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 9500 mg/kg ^[2]	Eye (human): 8 mg - mild
	Oral (rat) LD50: 5130 mg/kg ^[2]	Eye (rabbit): 500 mg/24hr - mild
		Skin (rabbit): 238 mg - mild
		Skin (rabbit): 500 mg (open)-mild
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

PHOSPHORIC ACID	phosphoric acid (85%)
ACETIC ACID GLACIAL	Prolonged or repeated exposure to acetic acid may produce irritation and/ or corrosion at the site of contact as well as systemic toxicity. Prolonged inhalation exposure results in muscle imbalance, increase in blood cholinesterase activity, decrease in albumin and decreased growth but no reproductive or foetal toxicity, according to animal testing.
(C10-16)ALKYLBENZENESULFONIC ACID	Linear alkyl benzene sulfonates are derived from strong corrosive acids. Animal testing has shown they can cause skin reactions, eye irritation, sluggishness, passage of frequent watery stools, weakness and may lead to death. They may also react with surfaces of the mouth and intestines, depending on the concentration exposed to. There is no evidence of harm to the unborn baby or tendency to cause cancer.

SULFURIC ACID	<p>WARNING: For inhalation exposure <u>ONLY</u>: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS</p> <p>Occupational exposures to strong inorganic acid mists of sulfuric acid:</p>
DIPROPYLENE GLYCOL MONOMETHYL ETHER	<p>For propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on the reproductive organs, the developing embryo and foetus, blood or thymus gland, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces an alkoxyacetic acid. The reproductive and developmental toxicities of the lower molecular weight homologues in the ethylene series are due specifically to the formation of methoxyacetic and ethoxyacetic acids. Longer chain homologues in the ethylene series are not associated with reproductive toxicity, but can cause haemolysis in sensitive species, also through formation of an alkoxyacetic acid. The predominant alpha isomer of all the PGEs (which is thermodynamically favoured during manufacture of PGEs) is a secondary alcohol incapable of forming an alkoxypropionic acid.</p>
PHOSPHORIC ACID & (C10-16)ALKYLBENZENESULFONIC ACID	<p>No significant acute toxicological data identified in literature search.</p>
PHOSPHORIC ACID & ACETIC ACID GLACIAL	<p>For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.</p>
PHOSPHORIC ACID & ACETIC ACID GLACIAL & (C10-16)ALKYLBENZENESULFONIC ACID & SULFURIC ACID & DIPROPYLENE GLYCOL MONOMETHYL ETHER	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p>
(C10-16)ALKYLBENZENESULFONIC ACID & DIPROPYLENE GLYCOL MONOMETHYL ETHER	<p>The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p>

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity					
Gun Powder Missile	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
phosphoric acid	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	75.1mg/L	2
	EC50	48	Crustacea	>5.62mg/L	2
	EC50	72	Algae or other aquatic plants	15.29mg/L	2
	EC10	72	Algae or other aquatic plants	37.7mg/L	2
	NOEC	72	Algae or other aquatic plants	3.71mg/L	2
acetic acid glacial	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2
	EC50	48	Crustacea	>1-mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	72	Algae or other aquatic plants	1-mg/L	2
(C10-16)alkylbenzenesulfonic acid	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	1.67mg/L	2
	EC50	48	Crustacea	2.5mg/L	2

	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	720	Crustacea	0.046mg/L	2
sulfuric acid	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	=8mg/L	1
	EC50	48	Crustacea	=42.5mg/L	1
	EC50	72	Algae or other aquatic plants	>100mg/L	2
	NOEC	Not Available	Crustacea	0.15mg/L	2
dipropylene glycol monomethyl ether	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-930mg/L	2
	EC50	48	Crustacea	1-930mg/L	2
	EC50	72	Algae or other aquatic plants	6-999mg/L	2
	NOEC	528	Crustacea	>=0.5mg/L	2
Legend: <i>Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data</i>					

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and /or delayed, to the structure and/ or functioning of natural ecosystems.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Prevent, by any means available, spillage from entering drains or water courses.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
phosphoric acid	HIGH	HIGH
acetic acid glacial	LOW	LOW
dipropylene glycol monomethyl ether	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
phosphoric acid	LOW (LogKOW = -0.7699)
acetic acid glacial	LOW (LogKOW = -0.17)
dipropylene glycol monomethyl ether	LOW (BCF = 100)

Mobility in soil

Ingredient	Mobility
phosphoric acid	HIGH (KOC = 1)
acetic acid glacial	HIGH (KOC = 1)
dipropylene glycol monomethyl ether	LOW (KOC = 10)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none">▶ Recycle wherever possible.▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.▶ Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).▶ Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

	A diamond-shaped hazard label with a black border. Inside, there is a black silhouette of a person being corroded by a liquid dripping from a test tube. Below the silhouette is the number '8'.
--	--

Marine Pollutant	NO
HAZCHEM	2X

Land transport (ADG)

UN number	1760
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains (C10-16)alkylbenzenesulfonic acid, phosphoric acid, sulfuric acid and acetic acid glacial)
Transport hazard class(es)	Class : 8 Subrisk : Not Applicable
Packing group	III
Environmental hazard	Not Applicable
Special precautions for user	Special provisions : 223 274 Limited quantity : 5 L

Air transport (ICAO-IATA / DGR)

UN number	1760
UN proper shipping name	Corrosive liquid, n.o.s. * (contains (C10-16)alkylbenzenesulfonic acid, phosphoric acid, sulfuric acid and acetic acid glacial)
Transport hazard class(es)	ICAO/IATA Class : 8 ICAO / IATA Subrisk : Not Applicable ERG Code : 8L
Packing group	III
Environmental hazard	Not Applicable
Special precautions for user	Special provisions : A3 A803 Cargo Only Packing Instructions : 856 Cargo Only Maximum Qty / Pack : 60 L Passenger and Cargo Packing Instructions : 852 Passenger and Cargo Maximum Qty / Pack : 5 L Passenger and Cargo Limited Quantity Packing Instructions : Y841 Passenger and Cargo Limited Maximum Qty / Pack : 1 L

Sea transport (IMDG-Code / GGVSee)

UN number	1760
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains (C10-16)alkylbenzenesulfonic acid, phosphoric acid, sulfuric acid and acetic acid glacial)
Transport hazard class(es)	IMDG Class : 8 IMDG Subrisk : Not Applicable
Packing group	III
Environmental hazard	Not Applicable
Special precautions for user	EMS Number : F-A , S-B Special provisions : 223 274 Limited Quantities : 5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

PHOSPHORIC ACID IS FOUND ON THE FOLLOWING REGULATORY LISTS	
Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	GESAMP/EHS Composite List - GESAMP Hazard Profiles
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	IMO IBC Code Chapter 17: Summary of minimum requirements
Australia Exposure Standards	IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Inventory of Chemical Substances (AICS)	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
ACETIC ACID GLACIAL IS FOUND ON THE FOLLOWING REGULATORY LISTS	

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	GESAMP/EHS Composite List - GESAMP Hazard Profiles
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	IMO IBC Code Chapter 17: Summary of minimum requirements
Australia Exposure Standards	IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards
Australia Inventory of Chemical Substances (AICS)	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	

(C10-16)ALKYLBENZENESULFONIC ACID IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	International Maritime Dangerous Goods Requirements (IMDG Code)
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations
Australia Inventory of Chemical Substances (AICS)	

SULFURIC ACID IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List	IMO IBC Code Chapter 17: Summary of minimum requirements
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
Australia Exposure Standards	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Inventory of Chemical Substances (AICS)	International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft
Chemical Footprint Project - Chemicals of High Concern List	International Maritime Dangerous Goods Requirements (IMDG Code)
GESAMP/EHS Composite List - GESAMP Hazard Profiles	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

DIPROPYLENE GLYCOL MONOMETHYL ETHER IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	IMO IBC Code Chapter 17: Summary of minimum requirements
Australia Inventory of Chemical Substances (AICS)	IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix B (Part 3)	IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO
GESAMP/EHS Composite List - GESAMP Hazard Profiles	

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (phosphoric acid; acetic acid glacial; dipropylene glycol monomethyl ether; sulfuric acid; (C10-16)alkylbenzenesulfonic acid)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No ((C10-16)alkylbenzenesulfonic acid)
Vietnam - NCI	Yes
Russia - ARIPS	No ((C10-16)alkylbenzenesulfonic acid)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	26/09/2024
Initial Date	13/04/2015

SDS Version Summary

Version	Issue Date	Sections Updated
3.1.1.1	14/04/2015	Acute Health (inhaled), Chronic Health, Classification, Ingredients, Use
8.1.1.1	26/09/2024	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or

Gun Powder Missile

other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.