

# SAFETY DATA SHEET.



Issuing date 03/01/2022

Revision Date 03/01/2022

Version 2

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product name TOTAL RELEASE BLACK DIAMOND

### Recommended use of the chemical and restrictions on use

Product code HT 19030

Product Type Extremely flammable aerosol

Synonyms None

### Supplier's details

Recommended Use Air freshener.  
Uses advised against No information available

#### Manufactured For:

Hi-Tech Industries  
33106 W. 8 Mile  
Farmington, MI 48336  
Company Telephone: 248-358-2626

Chemical Emergency Phone Number INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

##### **Hazard Statements**

Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Extremely flammable aerosol  
Contains gas under pressure; may explode if heated



**Appearance** Clear

**Physical state** Aerosol

**Odor** Solvent

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use

#### **Precautionary Statements - Response**

Specific treatment (see first aid on this label)  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water.  
Take off contaminated clothing and wash before reuse  
If skin irritation occurs: Get medical advice/attention  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER or doctor/physician if you feel unwell

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
Store locked up  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None

**Other information**

3.9E-06% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	70-80
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
PROPYLENE GLYCOL	57-55-6	1-10

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES****First aid measures for different exposure routes**

<b>General advice</b>	Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.
<b>Ingestion</b>	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician or Poison Control Center immediately.

**Most important symptoms/effects, acute and delayed**

<b>Main Symptoms</b>	Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May be harmful if swallowed.
----------------------	---

**Indication of immediate medical attention and special treatment needed, if necessary**

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

water fog. Dry chemical. Foam. Carbon dioxide (CO<sub>2</sub>). Cool containers / tanks with water spray.

**Unsuitable Extinguishing Media** Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

**Specific hazards arising from the chemical**

Extremely flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures****Personal precautions**

Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mists. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling. Ensure adequate ventilation.

**Environmental precautions****Environmental precautions**

Report spills as required by local and federal regulations. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods and materials for containment and cleaning up****Methods for Containment**

Prevent further leakage or spillage if safe to do so. Soak up condensate with inert absorbent material and collect in ventilated waste container for disposal.

**Methods for cleaning up**

Contain liquid and collect with an inert, non-combustible material. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

**7. HANDLING AND STORAGE****Precautions for safe handling****Advice on safe handling**

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid contact with skin and eyes. Avoid breathing vapors or mist. Contents under pressure. Do not puncture or incinerate container. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Do not lay on its side. Store in a cool place.

**Conditions for safe storage, including any incompatibilities****Technical measures/Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

**Incompatible products**

Strong acids, alkalis, or oxidizing agents.

**Aerosol Level**

3

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety &amp; Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls**Engineering Measures**

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment**Eye/Face Protection** Safety glasses with side-shields.**Skin and body protection** Chemical resistant apron. Protective gloves.**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice.**9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties

<b>Physical state</b>	Aerosol	<b>Odor</b> <b>Odor Threshold</b>	Solvent No information available
<b>Appearance</b>	Clear		
<b>Color</b>	clear		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	<b>• Methods</b>
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-97 °C / -143 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		

**Flammability Limits in Air**

upper flammability limit	No information available
lower flammability limit	No information available
<b>Vapor pressure</b>	No information available
<b>Vapor density</b>	No information available
<b>Specific Gravity</b>	0.762
<b>Water solubility</b>	Practically insoluble
<b>Partition coefficient: n-octanol/water</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>Explosive properties</b>	No information available

**Other information**

<b>VOC Content(%)</b>	18.92
-----------------------	-------

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Strong acids, alkalis, or oxidizing agents.

**Hazardous Decomposition Products**

Carbon oxides.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

**Inhalation** Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components. May cause irritation of respiratory tract. Avoid breathing vapors or mists.

**Eye contact** Irritating to eyes. Avoid contact with eyes.

**Skin contact** Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Avoid contact with skin.

**Ingestion** May be harmful or fatal if swallowed.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg	20,000 mg/kg (Rabbit)	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
PROPYLENE GLYCOL 57-55-6	= 20000 mg/kg ( Rat )	= 20800 mg/kg ( Rabbit )	-

Information on toxicological effects**Symptoms**

Inhalation may cause nose, throat, and respiratory tract irritation. Irritation to skin and eyes. May be harmful if swallowed.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Skin corrosion/irritation**

Irritating to skin.

**Eye damage/irritation**

Irritating to eyes.

**Irritation**

Irritating to eyes, respiratory system and skin.

**Sensitization**

No information available.

**Germ Cell Mutagenicity**

No information available.

**Carcinogenicity**

There are no known carcinogenic chemicals in this product.

**Reproductive toxicity**

The ingredients are not reproductive hazards.

**Specific target organ systemic toxicity (single exposure)**

May cause respiratory irritation. May cause drowsiness and dizziness.

**Specific target organ systemic toxicity (repeated exposure)**

None under normal use conditions.

**Target Organ Effects**

Central nervous system, Eyes, Respiratory system, Skin.

**Neurological effects**

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

**Aspiration hazard**

Not applicable.

Numerical measures of toxicity - Product Information**Unknown Acute Toxicity**

3.9E-06% of the mixture consists of ingredient(s) of unknown toxicity

**The following values are calculated based on chapter 3.1 of the GHS document .****ATEmix (oral)**

61667 mg/kg

**12. ECOLOGICAL INFORMATION**Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
PROPYLENE GLYCOL 57-55-6	19000 mg/L EC50 Pseudokirchneriella subcapitata 96h	41 - 47 mL/L LC50 Oncorhynchus mykiss 96h static 51400 mg/L LC50 Pimephales promelas 96h static 51600 mg/L LC50 Oncorhynchus mykiss 96h static 710 mg/L LC50 Pimephales promelas 96h	-	1000 mg/L EC50 Daphnia magna 48h Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow

ACETONE 67-64-1	-0.24
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8

Other adverse effects No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment

**Waste Disposal Methods** Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not re-use empty containers.

### 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

**IMDG** UN1950, AEROSOLS, 2.1, LTD. QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	X	X	X	X	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	Not listed	X	X	X	X
PROPYLENE GLYCOL	X	X	X	X	X	X	X	X

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

#### U.S. Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product does not contain any known Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
PROPYLENE GLYCOL 57-55-6	X		X

EPA Pesticide Registration Number Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

A Compressed gases  
B5 Flammable aerosol  
D2B Toxic materials

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health Hazard</b> 2	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Physical and chemical hazards</b> -
<b><u>HMIS</u></b>	<b>Health Hazard</b> 2	<b>Flammability</b> 4	<b>Physical Hazard</b> 1	<b>Personal protection</b> B

Prepared By Regulatory Affairs  
Issuing date 03/01/2022  
Revision Date 03/01/2022  
Revision Note

No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet